

## Cl06 Series 2.00mm(.079") Wire to Board Connectors Housing & Terminal

- With locking latch provides secure mating
- Mate with Cl06 Header
- O Can be used with Cl06 Crimp Clip Terminal
- O Insulator: Nylon 66 UL 94V-0, Color Nature



.051

Last Circuit





1.5

1st Circuit

ccc

0.5 .020 TYP.2











3.4	2.8
	: A-A

Circuits	Dimension		
	А	В	
2	2.0(.079)	4.6(.181)	
3	4.0(.157)	6.6(.260)	
4	6.0(.236)	8.6(.339)	
5	8.0(.315)	10.6(.417)	
6	10.0(.394)	12.6(.496)	
7	12.0(.472)	14.6(.575)	
8	14.0(.551)	16.6(.654)	
9	16.0(.630)	18.6(.732)	
10	18.0(.709)	20.6(.811)	
11	20.0(.787)	22.6(.890)	
12	22.0(.866)	24.6(.969)	
13	24.0(.945)	26.6(1.047)	
14	26.0(1.024)	28.6(1.126)	
15	28.0(1.102)	30.6(1.205)	
16	30.0(1.181)	32.6(1.283)	





Wire Range	Insulation Diameter	Reel Q'ty
AWG #24~#30	0.80 (.031) Min. 1.45 (.057) MAX.	10,000 PCS.





## **Ordering Code**



- 1 Series No.
- 2 No. of Circuits: 02 to 16
- ③ S = Housing
- 4 Other Options: 0000 = Standard \*Special options consult manufacturer



- ① Series No.
- ② Type: T01 = AWG #24 ~ #30
- ③ Plating Code: 1 = Tin over Nickel
- 4 Material: P = Phosphor Bronze
- 5 Other Options: E0 = Standard