



A = 2.00 * No. of Spaces
 B = A + 2.0
 * Available in 4 through 80 circuits

Recommended P.C. Board Layout

Notes:

- * Material:
Contact: Brass
- * Pin overall Length 30.0mm Max.
- * For Lead Free Wave Flow Process

Ordering Code

CH71 ** * V A ** -NH
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② No. of Circuits
- ③ Plating Code:
1 = 3.05 μm(120 μ") Min. Matte Tin over 0.76 μm(30 μ") Nickel
2 = Gold flash plated over 1.27 μm(50 μ") Nickel
- ④ V = Straight
- ⑤ Insulation: A = Nylon 6T UL 94V-0, Color Black
- ⑥ Pin Length Option cord:
See Table PDF. File No. CH7101T
- ⑦ -NH = For Lead Free Wave Processes and Halogen-Free

Halogen-Free	Lead Free Process	RoHS Compliant
--------------	-------------------	----------------

4				DATE		UNIT: mm / inch	TITLE: 2.00MM(.079") STRAIGHT DUAL ROW BORAD MOUNT PIN HEADER	 瀚荃股份有限公司 CviLux Corporation
3			DRAWN BY: Aaron	11/30-16'	TOLERANCE UNLESS OTHERWISE SPECIFIED		MATERIAL:	
2			ENGINEER: Sun	12/06-16'	.X±0.30/.012	X:±1'	FINISH:	
1	Aaron	10/21-16'	ECNT116250/ECRB116072	CHECKED BY: Eisley	12/16-16'	.XX±0.20/.008	.X±	
SYM	NAME	DATE	REVISIONS	APPROVED BY: Eisley	12/16-16'	.XXX±0.10/ .004	.XX±	DRAWING NO. CH7124AB
								PART NO. CH71***VA**-NH
								SCALE 4 / 1
								SHEET 1 OF 1

CIVILUX CORP
 2016.12.22
 ISSUED