



Materials:

- \* Insulator: Glass filled polyester UL 94V-0
- \* Contacts: Copper alloy
- \* Shell: Steel, Tin plated as standard

Ordering Code:

CD67 09 P A 1 00  
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Contacts:
- ③ Contact type: P= Plug(Male)
- ④ Plating option:
  - 2= Gold flash plated over 1.27μm(50μ) Nickel
  - A= Selective Gold flash plated over 1.27μm(50μ) Nickel
  - B= Selective 0.38μm(15μ) Gold plated over 1.27μm(50μ) Nickel
  - C= Selective 0.76μm(30μ) Gold plated over 1.27μm(50μ) Nickel
- ⑤ Color: 1= Black
- ⑥ Other Option: 00= Standard

RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: D-SUB TOP ENTRY BOARD MOUNT MALE CONNECTOR	瀚荃股份有限公司 CviLux Corporation				
③				DRAWN BY: Sun	12/1 03'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:				DRAWING NO.	CD6702SD
②				ENGINEER: Eisley	12/2 03'	.X ± 0.30 / .012 X* ± 1"	FINISH:	SCALE	2 / 1	SHEET	1 OF 1	
①	SUN	12/01/03'	ECN03434	CHECKED BY: David	12/2 03'	.XX ± 0.20 / .010 .X* ±						
SYM	NAME	DATE	REVISIONS	APPROVED BY: David	12/3 03'	.XXX ± 0.10 / .004 .XX* ±						

CVILUX.CORP  
 2003.12.03  
 ISSUED