


Material:
 * Insulation: PBT+ 15% GF. UL 94V-0
 * Contact: Phosphor Bronze

Ordering Code:
 CS01 34 2 B 1 00
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Isulation high:
- ③ Plating option:
2= Gold flash plated over
1.27 μm(50 μ") Nickel
- ④ Contact type:
B= Open end
- ⑤ Color code:
1= Black ,3= Red ,7= Blue
- ⑥ Option:
00= Standard

RoHS Compliant

CVILUX CORP
 2019.08.22
 ISSUED

| | | | | | | | | | | | |
|-----|-------|----------|-----------------------|---------------------|----------|---|--|--|--------|-------|--------|
| ④ | Sun | 8/12/19' | ECNT119207 | | DATE | UNIT: mm / inch | TITLE: 2.00MM(.079") LOW PROFILE OPEN TOP SHUNT |  瀚荃股份有限公司 CviLux Corporation | | | |
| ③ | Enya | 5/8-13' | ECR13036-0/ECN13103-0 | DRAWN BY: Sun | 8/12-19' | TOLERANCE UNLESS OTHERWISE SPECIFIED | MATERIAL: | | | | |
| ② | Sandy | 5/5-09' | ECN09224 | ENGINEER: Sun | 8/12-19' | .X ± 0.30 / .012 .X' ± 1" | FINISH: | SCALE | 10 / 1 | SHEET | 1 OF 1 |
| ① | Sun | 9/30/05 | ECR05067-0/ECN05275 | CHECKED BY: Eisley | 8/16-19' | .XX ± 0.20 / .008 .X' ± | | | | | |
| SYM | NAME | DATE | REVISIONS | APPROVED BY: Eisley | 8/16-19' | .XXX ± 0.10 / .004 .XX' ± | | | | | |