



Notes:

- * Material:
Contact: Brass
- ⚠ * Pin overall Length 30.0mm Max.
- * For Lead Free Wave Flow Process

Ordering Code

CH11 ** * H A ** -NH
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② No. of Circuits
- ③ Plating Code:
1 = 2.54μm(100μ") Min. Tin Plated
over 1.27μm(50μ") Nickel(Matte Tin Plated)
2 = Gold flash plated
over 1.27μm(50μ") Nickel
- ④ H = Right angle
- ⑤ Insulation: A = Nylon 6T UL 94V-0, Color Black
- ⑥ Pin Length Option cord:
See Table PDF. File No. CH1103T
- ⑦ -NH = For Lead Free Wave Processes and
Halogen-Free

A = 2.0 * No. of Spaces
 B = A + 2.0
 * Available in 2 through 40 circuits

Recommended P.C. Board Layout

Halogen-Free

Lead Free Process

RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: 2.00MM(.079") RIGHT ANGLE	瀚荃股份有限公司 CviLux Corporation	
③					DRAWN BY: Aaron	TOLERANCE UNLESS OTHERWISE SPECIFIED	SINGLE ROW BORAD MOUNT PIN HEADER		
②	Aaron	10/21-16'	ECNT116250/ECRB116072	<div style="border: 2px solid red; border-radius: 50%; padding: 5px; display: inline-block; text-align: center;"> 2016.12.22 ISSUED </div>	ENGINEER: Sun	.X ± 0.30 / .012	X' ± 1'	DRAWING NO. CH1155SC	
①	Sun	10/6-08'	ECN08478/ECR08118-1		CHECKED BY: Eisley	12/06-16'	.XX ± 0.20 / .008		.X' ±
SYM	NAME	DATE	REVISIONS		APPROVED BY: Eisley	12/16-16'	.XXX ± 0.10 / .004	.XX' ±	SCALE 4 / 1
								SHEET 1 OF 1	