



Material: Nylon 66 UL 94V-0

Ordering Code

CI15 ** S 0000
 ① ② ③ ④

- ① Series No.
- ② No. of Circuits:
- ③ S= Connector housing
- ④ Color option: 0000= Nature (Standard)

Circuits	Dimension		
	A	B	C
2	1.50(.059)	3.5(.138)	4.50(.177)
3	3.00(.118)	5.0(.196)	6.00(.236)
4	4.50(.177)	6.5(.255)	7.50(.295)
5	6.00(.236)	8.0(.314)	9.00(.354)
6	7.50(.300)	9.5(.374)	10.50(.413)
7	9.00(.354)	11.0(.433)	12.00(.472)
8	10.50(.413)	12.5(.492)	13.50(.531)
9	12.00(.472)	14.0(.551)	15.00(.591)
10	13.50(.531)	15.5(.610)	16.50(.650)
11	15.00(.590)	17.0(.669)	18.00(.709)
12	16.50(.649)	18.5(.728)	19.50(.768)
13	18.00(.708)	20.0(.787)	21.00(.827)
14	19.50(.767)	21.5(.846)	22.50(.886)
15	21.00(.826)	23.0(.905)	24.00(.945)

Halogen-Free **RoHS Compliant**

- ④
- ③
- ②
- ①

CVILUX.CORP
2006.12.28
ISSUED

DRAWN BY: Hank
 ENGINEER: Eisley
 CHECKED BY: David
 APPROVED BY: Alex

DATE: 12/22-06'
 UNIT: mm / inch
 TOLERANCE UNLESS OTHERWISE SPECIFIED
 .X ± 0.30/.012 X' ± 1"
 .XX ± 0.20/.008 .X' ±
 .XXX ± 0.10/.004 .XX' ±

TITLE: 1.50MM(.024")
 CRIMP TERMINAL HOUSING
 MATERIAL:
 FINISH:



瀚荃股份有限公司
 CviLux Corporation

DRAWING NO. CI1512SA PART NO. CI15**S0000
 SCALE 6 / 1 SHEET 1 OF 1