



Recommended P.C. Board Layout

- Material:
- \* Insulation: Nylon 6T
  - \* Contact: Brass
  - \* Circuit Pattern Schedule: See Drawing No: CP0110S\*
  - \* For Lead Free wave flow process

Ordering Code:

CP-01 3 \*\* 1 \* 0 -NH  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② Type of Connector: 3= Straight PCB mount header
- ③ No. of Circuits: See below table
- ④ Plating Code:  
 1= 2.54μm(100μ”) Matte Tin over 0.76μm(30μ”) Nickel  
 2= Gold flash plated over 1.27μm(50μ”) Nickel
- ⑤ Variation:  
 3= Without mounting pegs  
 5= With mounting pegs
- ⑥ Option:  
 0= Standard
- ⑦ Other option:  
 -NH= For Lead Free IR Processes and Halogen-Free

Halogen-Free  
 Lead Free Process  
 RoHS Compliant

④						DATE	UNIT: mm / inch	TITLE: STRAIGHT HEADER CP-01 POWER CONNECTOR	瀚荃股份有限公司 CviLux Corporation
③						DATE	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②						DATE	.X ± 0.38/.015 X' ± r	FINISH:	
①	Hank	10/28-16	ECNT116260			DATE	.XX ± 0.25/.010 X' ±	DRAWING NO. CP01266SB PART NO. CP-013****0-NH	
SYM	NAME	DATE	REVISIONS			DATE	.XXX ± 0.10/.004 XX' ±	SCALE 2 / 1 SHEET 1 OF 1	

CVILUX CORP  
 2016.11.03  
 ISSUED