

<b>ENGINEERING</b>	<b>PRODUCT SPECIFICATION</b>	<b>SPEC.NO.: SPCP007F</b>
<b>DEPT.</b>	<b>For CP33 Series Connector System</b>	<b>PAGE: 1/3</b>

1. SCOPE:

This specification contains the test requirement of subject connectors when tested under the condition and below standards base on CviLux test procedure

2. APPLICABLE STANDARDS:

MIL - STD - 202                      Methods for test of connectors for electronic equipment  
MIL - STD - 1344                    Test methods for electrical connectors

3. APPLICABLE SERIES NO.: CP33 Series

4. SHAPE, CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. ACCOMMODATED P.C.BOARD

6.1 Thickness: 1.6 mm (.063")

6.2 P.C. Board Layout: See attached drawings



REVIEWED :   Alex      APPROVED :   David      VERIFIED :   Jim   .

<b>ENGINEERING</b> <b>DEPT.</b>	<b>PRODUCT SPECIFICATION</b> <b>For CP33 Series Connector System</b>	<b>SPEC.NO.: SPCP007F</b>
		<b>PAGE: 2/3</b>

**7. ELECTRICAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
7.1	Rated current and voltage		6A 250V AC (r.m.s.)
7.2	Contact resistance	Dry circuit of DC 20 mV max. , 100 mA max.	Less than 20 mΩ
7.3	Dielectric strength	When applied AC 1500 V 1 minute between adjacent terminal	No change
7.4	Insulation resistance	When applied DC 500 V between adjacent terminal or ground	More than 1000 MΩ


**8. MECHANICAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Wire size	Specified wire size	Accepts AWG#18
8.2	Contact retaining force in insulator	Retention speed 25± 3 mm per minute from housing	More than 4.0 Kgf
8.3	Single contact insertion force	Measure force to insertion using plug terminal at speed 25± 3 mm per minute	2.5 Kgf max.
8.4	Single contact withdrawal force	Measure force to withdrawal using plug terminal at speed 25± 3 mm per minute	400 gram min.
8.5	Durability	Connector shall be subjected to 100 cycles of insertion and withdrawal	Contact resistance: Less than twice of initial

**9. ENVIRONMENTAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Temperature rise	Then carried the rated current	30°C max.
9.2	Vibration	1.5 mm 10-55-10 HZ / minute each 2 hours for X , Y and Z directions	Appearance: No damage Discontinuity: 1 micro second max.
9.3	Solder ability	<b>Tin-Lead Process:</b> Soldering time: 5 ± 0.5 second Soldering pot: 230 ± 5°C	Minimum: 90% of immersed area
9.4	Resistance to soldering heat	<b>Tin-Lead Process:</b> Soldering time: 5 ± 0.5 second Soldering pot: 240 ± 5°C	No damage

	ITEM	TEST CONDITION	REQUIREMENT
--	------	----------------	-------------



<b>ENGINEERING DEPT.</b>	<b>PRODUCT SPECIFICATION For CP33 Series Connector System</b>	<b>SPEC.NO.: SPCP007F</b>
		<b>PAGE: 3/3</b>

9.5	Heat aging	85 ± 2°C , 96 hours	No damage
9.6	Humidity	40 ± 2°C , 90-95% RH , 96 hours measurement must be taken within 30 min. after tested	Appearance: No damage Contact resistance: Less than twice of initial Dielectric strength: To pass para 7-3
9.7	Temperature cycling	One cycle consists of : (1)-55 <sup>+0</sup> °C , 30 min. -3 (2)Room temp. 10-15 min. (3) 85 <sup>+3</sup> °C , 30 min. -0 (4)Room temp. 10-15 min.	Appearance: No damage Contact resistance: Less than twice of initial
9.8	Salt spray	Temperature: 35 ± 3°C Solution: 5 ± 1% Spray time: 48 ± 4 hours Measurement must be taken after water rinse	Appearance: No damage Contact resistance: Less than twice of initial

10. AMBIENT TEMPERATURE RANGE: -25 to + 85°C