

<b>ENGINEERING DEPT.</b>		<b>PRODUCT SPECIFICATION</b> <b>For CF23 Series Connector System</b>	<b>SPEC.NO.: SPCF020G</b>
<b>REVISIONS</b>	<b>ECNT120078</b>		<b>PAGE: 1/4</b>

1. SCOPE:

This specification contains the test requirement of subject connectors when tested under the condition and inserted on the specified size FPC and FFC

2. APPLICABLE STANDARDS:

MIL - STD - 202	Methods for test of connectors for electronic equipment
EIA - 364	Test methods for electrical connectors
J-STD-020	Resistance to soldering Temperature for through hole Mounted Devices
SS-00254	Test methods for electronic components ,LEAD-FREE soldering Part design standards

3. APPLICABLE SERIES NO.: **CF23 Series**

4. SHAPE, CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. ACCOMMODATED P.C.BOARD

6.1 Thickness: 0.5 mm (.020") ~ 2.0 mm (.079")

6.2 P.C. Board Layout: See attached drawings

7. ACCOMMODATED FPC/FFC THICKNESS

0.3 +0.04/-0.01 mm (.012+.002/-0")

REVIEWED : Eisley APPROVED : Sun VERIFIED : Michelle

<b>ENGINEERING DEPT.</b>		<b>PRODUCT SPECIFICATION</b> <b>For CF23 Series Connector System</b>	<b>SPEC.NO.: SPCF020G</b>
<b>REVISIONS</b>	<b>ECNT120078</b>		<b>PAGE: 2/4</b>

8. ELECTRICAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Rated current and voltage		0.4A max. 50V AC/DC max.
8.2	Contact resistance	Dry circuit of DC 20 mV max. , 100 mA max.	Less than 30 mΩ
8.3	Dielectric strength	When applied AC 250 V 1 minute between adjacent terminal	No change
8.4	Insulation resistance	When applied DC 500 V between adjacent terminal or ground	More than 100 MΩ

9. MECHANICAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Contact retaining force in insulator	Retention speed 25± 3 mm per minute from housing	More than 80 gf
9.2	FFC / FPC withdrawal force (Reference data)	Measure force to withdrawal using 0.30 mm thickness FPC / FFC at speed 25± 3 mm per minute	(0.02× no. of Contacts) Kgf min.
9.3	Durability	Connector shall be subjected to 20 cycles of insertion and withdrawal	Contact resistance: Less than twice of initial

10. ENVIRONMENTAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
10.1	Temperature rise	Then carried the rated current	30°C max.
10.2	Vibration	1.5 mm 10-55-10 HZ / minute each 2 hours for X , Y and Z directions	Appearance: No damage Discontinuity: 1 micro second max.
10.3	Solder ability	<b>Tin-Lead Process:</b> Soldering time: 5 ± 0.5 second Soldering pot: 230 ± 5°C <b>Lead-Free Process:</b> Soldering time: 3 ± 0.5 second Soldering pot: 245 ± 5°C	Minimum: 90% of immersed area

<b>ENGINEERING DEPT.</b>		<b>PRODUCT SPECIFICATION</b> <b>For CF23 Series Connector System</b>	<b>SPEC.NO.: SPCF020G</b>
<b>REVISIONS</b>	<b>ECNT120078</b>		<b>PAGE: 3/4</b>


	ITEM	TEST CONDITION	REQUIREMENT
10.4	Resistance to soldering heat	<p><b>Tin-Lead Process:</b> Refer Reflow temperature profile(12.1) Soldering time: 10 second Max. Soldering pot: 230 ± 5 °C</p> <p><b>Lead-Free Process:</b> Soldering time: 20 second Max. Soldering pot: 250~260°C Refer Reflow temperature profile(12.2)</p>	No damage
10.5	Heat aging	85 ± 2°C , 96 hours	No damage
10.6	Humidity	40 ± 2°C , 90-95% RH , 96 hours measurement must be taken within 30 min. after tested	<p>Appearance: No damage</p> <p>Contact resistance: Less than twice of initial</p> <p>Dielectric strength: To pass para 8-3</p>
10.7	Temperature cycling	<p>One cycle consists of :</p> <p>(1) <math>-55_{-3}^{+0}</math> °C , 30 min.</p> <p>(2) Room temp. 10-15 min.</p> <p>(3) <math>85_{-0}^{+3}</math> °C , 30 min.</p> <p>(4) Room temp. 10-15 min.</p>	<p>Appearance: No damage</p> <p>Contact resistance: Less than twice of initial</p>
10.8	Salt spray	<p>Temperature: 35 ± 3°C</p> <p>Solution: 5 ± 1%</p> <p>Spray time: 48 ± 4 hours (Stamping before plated)</p> <p>Spray time: 24 ± 4 hours (Stamping after plated)</p> <p>Mate connectors and expose to the following salt mist conditions. Upon completion of the exposure period, salt deposits shall be removed by a gentle wash or dip in running water and dried naturally, after which the specified measurements shall be performed. The specimens shall be suspended from the top using waxed twine, string or nylon thread.</p> <p>The test only define the plating area, without plating area (as copper cross section) will not be defined.</p> <p>(EIA 364-26B / MIL-STD-202 Method 101)</p>	<p>Appearance: No damage</p> <p>Contact resistance: Less than twice of initial</p>

ENGINEERING DEPT.		PRODUCT SPECIFICATION For CF23 Series Connector System	SPEC.NO.: SPCF020G
REVISIONS	ECNT120078		PAGE: 4/4

11. AMBIENT TEMPERATURE RANGE: -25 to + 85°C

12. Recommended IR Reflow Temperature Profile:

12.1 Using Typical Solder Paste



12.2 Using Lead-Free Solder Paste

