

<b>ENGINEERING DEPT.</b>		<b>PRODUCT SPECIFICATION</b> <b>For 2.54 mm (.100") Board to Board</b> <b>Connectors of System CB39</b>	<b>SPEC.NO.:</b> SPCB024C
<b>REVISIONS</b>	ECNT120076		<b>PAGE:</b> 1/4

1. SCOPE:

This specification contains the test requirement of subject connectors when tested under the condition and below standards base on CviLux test procedure

2. APPLICABLE STANDARDS:

MIL - STD - 202                      Methods for test of connectors for electronic equipment  
EIA – 364                              Test methods for electrical connectors

3. APPLICABLE SERIES NO.: **CB39 Series**

4. SHAPE, CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. ACCOMMODATED P.C. BOARD

1.6 mm (.063")

REVIEWED : Eisley    APPROVED : Eisley    VERIFIED : Michelle .

<b>ENGINEERING DEPT.</b>		<b>PRODUCT SPECIFICATION</b> <b>For 2.54 mm (.100") Board to Board</b> <b>Connectors of System CB39</b>	<b>SPEC.NO.:</b> SPCB024C
<b>REVISIONS</b>	ECNT120076		<b>PAGE:</b> 2/4

**7. ELECTRICAL PERFORMANCE:**

	ITEM	TEST CONDITION	
7.1	Rated current and voltage		3A 250V AC (r.m.s.)
7.2	Contact resistance	Dry circuit of DC 20 mV max. 100 mA max.	Less than 20 mΩ
7.3	Dielectric strength	When applied AC 1000 V 1 minute between adjacent terminal	No change
7.4	Insulation resistance	When applied DC 500 V between adjacent terminal or ground	More than 1000 MΩ

**8. MECHANICAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Contact retaining force in insulator	Retention speed 25± 3 mm per minute form housing	More than 800 gram
8.2	Single contact insertion force	Measure force to insertion using 0.64 mm square pin at speed 25± 3 mm per minute	800 gram max.
8.3	Single contact withdrawal force	Measure force to withdrawal using 0.64 mm square pin at speed 25± 3 mm per minute	30 gram min.
8.4	Durability	Connector shall be subjected to 100 cycles of insertion and withdrawal	Contact resistance: Less than twice of initial

**9. ENVIRONMENTAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Vibration	1.5 mm 10 - 55 - 10 HZ/minute each 2 hours for X,Y and Z directions	Appearance: No damage Discontinuity: 1 micro second max.
9.2	Solderability	<b>Tin-Lead Process:</b> Soldering time: 5 ± 0.5 second Soldering pot: 230 ± 5°C  <b>Lead-Free Process:</b> Soldering time: 3 ± 0.5 second Soldering pot: 245 ± 5°C	Minimum: 90% of immersed area

<b>ENGINEERING DEPT.</b>		<b>PRODUCT SPECIFICATION</b> <b>For 2.54 mm (.100") Board to Board</b> <b>Connectors of System CB39</b>	<b>SPEC.NO.:</b> SPCB024C
<b>REVISIONS</b>	ECNT120076		<b>PAGE:</b> 3/4

	ITEM	TEST CONDITION	REQUIREMENT
9.3	Resistance to soldering heat	<b>Tin-Lead Process:</b> Soldering time: 5 ± 0.5 second Soldering pot: 240 ± 5°C <b>Lead-Free Process:</b> Soldering time: 5 ± 0.5 second Soldering pot: 260 ± 5°C	No damage
9.4	Heat aging	105± 2°C, 96 hours	No damage
9.5	Humidity	40±2°C, 90-95% RH, 96 hours measurement must be taken within 30 min. after tested	Appearance: No damage Contact resistance: Less than twice of initial Dielectric strength: To pass para 7-3
9.6	Temperature cycling	One cycle consists of : (1) -55 <sup>+0</sup> / <sub>-3</sub> °C , 30 min. (2)Room temp. 10-15 min. (3) 85 <sup>+3</sup> / <sub>-0</sub> °C , 30 min. (4)Room temp. 10-15 min.	Appearance: No damage Contact resistance: Less than twice of initial

<b>ENGINEERING DEPT.</b>		<b>PRODUCT SPECIFICATION</b> <b>For 2.54 mm (.100") Board to Board</b> <b>Connectors of System CB39</b>	<b>SPEC.NO.:</b> SPCB024C
<b>REVISIONS</b>	ECNT120076		<b>PAGE:</b> 4/4

	ITEM	TEST CONDITION	REQUIREMENT
9.7	Salt spray	<p>Temperature: <math>35 \pm 3^{\circ}\text{C}</math></p> <p>Solution: <math>5 \pm 1\%</math></p> <p>Spray time: <math>48 \pm 4</math> hours (Stamping before plated)</p> <p>Spray time: <math>24 \pm 4</math> hours (Stamping after plated)</p> <p>Mate connectors and expose to the following salt mist conditions. Upon completion of the exposure period, salt deposits shall be removed by a gentle wash or dip in running water and dried naturally, after which the specified measurements shall be performed.</p> <p>The specimens shall be suspended from the top using waxed twine, string or nylon thread.</p> <p>The test only define the plating area, without plating area (as copper cross section) will not be defined.</p> <p>(EIA 364-26B / MIL-STD-202 Method 101)</p>	<p>Appearance: No damage</p> <p>Contact resistance: Less than twice of initial</p>

10. AMBIENT TEMPERATURE RANGE:  $-40$  to  $+105^{\circ}\text{C}$