

ENGINEERING DEPT.		PRODUCT SPECIFICATION For 1.27 mm (.050") Pin Header of System CH51	SPEC.NO.: SPCH034C
REVISIONS	ECNT120128		PAGE: 1/3

1. SCOPE:

This specification contains the test requirement of subject pin headers when tested under the condition and below standards base on CviLux test procedure

2. APPLICABLE STANDARDS:

MIL - STD - 202	Methods for test of connectors for electronic equipment
EIA - 364	Test methods for electrical connectors
JIS - C - 5402	Methods for test of connectors for electronic equipment
UL 94	Test for flammability of plastic materials for parts in devices and appliance
J-STD-020	Resistance to soldering Temperature for through hole Mounted Devices
SS-00254	Test methods for electronic components ,LEAD-FREE soldering Part design standards

3. APPLICABLE SERIES NO.: **CH51 SERIES**

4. SHAPE, CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. MATERIALS

(P.C. Board on which the Pin Header are installed), 0.8 mm (.031") ~ 1.6 mm (.063")

REVIEWED : Eisley APPROVED : Sun VERIFIED : Michelle .

ENGINEERING DEPT.		PRODUCT SPECIFICATION For 1.27 mm (.050") Pin Header of System CH51	SPEC.NO.: SPCH034C
REVISIONS	ECNT120128		PAGE: 2/3

7. ELECTRICAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
7.1	Rated current and voltage		1A 250V AC (r.m.s.)
7.2	Contact resistance	Dry circuit of DC 20 mV max. , 100 mA max	Less than 20 mΩ
7.3	Dielectric strength	When applied AC 600 V 1minute between adjacent terminal	No change
7.4	Insulation resistance	When applied DC 500 V between adjacent terminal or ground	More than 1000 MΩ

8. MECHANICAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Pin retention force	Push pin from insulator base at speed 25± 3 mm per minute	More than 200 gram

9. ENVIRONMENTAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Solder ability	Soldering time: 3 ± 0.5 second Soldering pot: 245 ± 5°C	Minimum: 90% of immersed area
9.2	Resistance to soldering heat	DIP Type: Soldering time: 5 ± 0.5 second Soldering pot: 260 ± 5°C SMT Type: Soldering time: 20 second Max. Soldering pot: 250~260°C	No damage
9.3	Heat aging	105± 2°C, 96 hours	No damage
9.4	Humidity	40± 2°C, 90-95% RH, 96 hours measurement must be taken within 30 min. after tested	Appearance: No damage Contact resistance: Less than twice of initial Dielectric strength: To pass para 7-3
9.5	Temperature cycling	One cycle consists of : (1)-55 ⁺⁰ ₋₃ °C , 30 min. (2)Room temp. 10-15 min. (3) 85 ⁺³ ₋₀ °C , 30 min. (4)Room temp. 10-15 min.	Appearance: No damage Contact resistance: Less than twice of initial

ENGINEERING DEPT.	PRODUCT SPECIFICATION	SPEC.NO.: SPCH034C
REVISIONS	ECNT120128	For 1.27 mm (.050") Pin Header of System CH51
		PAGE: 3/3

ITEM	TEST CONDITION	REQUIREMENT
9.6	Salt spray Temperature: $35 \pm 3^{\circ}\text{C}$ Solution: $5 \pm 1\%$ Spray time: 48 ± 4 hours (Stamping before plated) Spray time: 24 ± 4 hours (Stamping after plated) Mate connectors and expose to the following salt mist conditions. Upon completion of the exposure period, salt deposits shall be removed by a gentle wash or dip in running water and dried naturally, after which the specified measurements shall be performed. The specimens shall be suspended from the top using waxed twine, string or nylon thread. The test only define the plating area, without plating area (as copper cross section) will not be defined. (EIA 364-26B / MIL-STD-202 Method 101)	Appearance: No damage Contact resistance: Less than twice of initial

10. AMBIENT TEMPERATURE RANGE:

-40 to + 105°C ; + 215°C intermittent (Vapor Phase Solder Reflow) for SMT type

11. Recommended IR Reflow Temperature Profile:

