


ENGINEERING	CRIMP SPECIFICATION	SPEC. No.:SCCI035C
DEPT.	For CI14T01****0 TERMINAL	PAGE: 1 / 1

1. Crimp height and width of crimped core should be set as required. (crimped height and width of wire barrel)
2. Crimp width of crimped sheath shall be adjusted according to the final out side diameter and the kind of electric wire, to the extent that sheathed wire won't be easily taken off from contact nor too much crimped. (crimped width of insulation barrel)



Subject : UL 10368(No Halogen) or equivalent type electric wire

AWG #	Conductor mm ²	Insulator Diameter	Applicator	Core crimp length	Dim. L
#28~#32	0.089 ~ 0.035	0.90 ~ 0.70mm	A01CI14T010	0.8 - 1.2 mm	0.2-0.4 mm

Wire Gage (AWG #)	Conductor Crimp Area		Insulator Crimp Area		Terminal Tensile Strength
	Width (1)	Height (2)	Width (3)	Height (4)	
#28	0.75~0.80	0.50~0.55	0.75~0.80	0.90~1.00	1.3 Kgf
#30		0.48~0.53	0.74~0.79		0.8 Kgf
#32		0.46~0.51			0.6 Kgf

DATE	REVISIONS	SPEC BY:	Ken
09/03-09'	ECN09452	CHKD BY:	Sun
08/04-16'	ECNT116169	APPR BY:	Eisley

