

<b>ENGINEERING</b>  <b>DEPT.</b>	<b>PRODUCT SPECIFICATION</b> <b>For CJ02,CJ04,CJ07 Series</b> <b>Board Mound Telephone Jack</b>	<b>SPEC.NO.: SPCJ060A</b>  <b>PAGE: 1 / 3</b>
--	---	---

1. SCOPE:

This specification contains the test requirement of subject connectors when tested under the condition and below standards base on CviLux test procedure

2. APPLICABLE STANDARDS:

MIL - STD - 202                      Methods for test of connectors for electronic equipment  
MIL - STD - 1344                    Test methods for electrical connectors

3. APPLICABLE SERIES NO.: CJ02\*\*\*1\*00-G, CJ046\*\*1\*00-G, CJ076\*\*\*\*\*-G

4. SHAPE, CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. ACCOMMODATED P.C.BOARD

6.1 Thickness: 1.6 mm (.063")

6.2 P.C. Board Layout: See attached drawings

REVIEWED : David    APPROVED : Eisley    VERIFIED : Sun .



<b>ENGINEERING</b>  <b>DEPT.</b>	<b>PRODUCT SPECIFICATION</b>  <b>For CJ02,CJ04,CJ07 Series</b> <b>Board Mound Telephone Jack</b>	<b>SPEC.NO.: SPCJ060A</b>
		<b>PAGE: 2 / 3</b>

**7. ELECTRICAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
7.1	Rated current and voltage		1.5A 125V AC (r.m.s.)
7.2	Contact resistance	Dry circuit of DC 20 mV max. 100 mA max.	Less than 40 mΩ(Initial) Less than 100 mΩ(Final)
7.3	Dielectric strength	When applied AC 1000 V 1 minute between adjacent terminal	No change
7.4	Insulation resistance	When applied DC 500 V between adjacent terminal or ground	More than 500 MΩ

**8. MECHANICAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Mating force	Measure force to mate samples at speed 25±3mm per minute with plug latch depressed	30N(3.06) Kgf max.
8.2	Retention force (Between the jack and plug)	Retention speed 25±3mm per minute from jack	50N(1.97) Kgf min.
8.3	Durability	Connector shall be subjected to 750 cycles of insertion and withdrawal	Contact resistance: Less than t Final

**9. ENVIRONMENTAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Vibration	1.5 mm 10 - 55 - 10 HZ/minute each 2 hours for X,Y and Z directions	Appearance: No damage Discontinuity: 1 micro second max.
9.2	Solder ability	Soldering time: 5±0.5 second Soldering pot: 245± 5°C	Minimum: 95% of immersed area
9.3	Resistance to soldering heat	Soldering time: 5±0.5 second Soldering pot: 260±5°C	No damage
9.4	Heat aging	85±2°C, 96 hours	No damage
9.5	Humidity	40±2°C, 90-95% RH, 96 hours measurement must be taken within 30 min. after tested	Appearance: No damage Contact resistance: Less than twice of initial Dielectric strength: To pass para 7-3



<b>ENGINEERING</b>	<b>PRODUCT SPECIFICATION</b> <b>For CJ02,CJ04,CJ07 Series</b> <b>Board Mound Telephone Jack</b>	<b>SPEC.NO.: SPCJ060A</b>
<b>DEPT.</b>		<b>PAGE: 3 / 3</b>

	ITEM	TEST CONDITION	REQUIREMENT
9.6	Temperature cycling	One cycle consists of : (1) $-40^{+0}_{-3}$ °C , 30 min. (2) Room temp. 10-15 min. (3) $85^{+3}_{-0}$ °C , 30 min. (4) Room temp. 10-15 min.	Appearance: No damage Contact resistance: Less than twice of initial
9.7	Salt spray	Temperature: $35 \pm 3$ °C Solution: $5 \pm 1$ % Spray time: $48 \pm 4$ hours Measurement must be taken after water rinse	Appearance: No damage Contact resistance: Less than Final

10. OPERATION TEMPERATURE RANGE:  $-40$  to  $+85$  °C ;  
STOCKPILE TEMPERATURE RANGE:  $-20$  to  $+60$  °C