

ENGINEERING DEPT.		PRODUCT SPECIFICATION For 2.00 mm (.079") Pin Header of System CH70	SPEC.NO.: SPCH078B
REVISIONS	ECNT120150		PAGE: 1/3

1. SCOPE:

This specification contains the test requirement of subject pin headers when tested under the condition and below standards base on CviLux test procedure

2. APPLICABLE STANDARDS:

MIL - STD - 202	Methods for test of connectors for electronic equipment
EIA 364	Test methods for electrical connectors
J-STD-020	Resistance to soldering Temperature for through hole Mounted Devices
SS-00254	Test methods for electronic components ,LEAD-FREE soldering Part design standards

3. APPLICABLE SERIES NO.: CH70**2V10A/ CH70**2M10A

4. SHAPE, CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. ACCOMMODATED P.C.BOARD

(P.C. Board on which the Pin Header are installed), 1.6 mm (.063")



REVIEWED : Eisley APPROVED : Sun VERIFIED : Jessie

ENGINEERING DEPT.		PRODUCT SPECIFICATION For 2.00 mm (.079") Pin Header of System CH70	SPEC.NO.: SPCH078B
REVISIONS	ECNT120150		PAGE: 2/3

7. ELECTRICAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
7.1	Rated current and voltage		2A 250V AC (r.m.s.)
7.2	Contact resistance	Dry circuit of DC 20 mV max. , 100 mA max.	Less than 20 mΩ
7.3	Dielectric strength	When applied AC 500 V 1minute between adjacent terminal	No change
7.4	Insulation resistance	When applied DC 500 V between adjacent terminal or ground	More than 5000 MΩ

8. MECHANICAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Pin retention force	Apply axial pull out force at 25± 3mm/min on the assembly in the housing	More than 0.8 Kgf

9. ENVIRONMENTAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Cold Resistance	-40± 3°C, 96 hours	Appearance: No damage Contact resistance Δ 20 mΩ change
9.2	Heat Resistance	105± 3°C, 96 hours	Appearance: No damage Contact resistance Δ 20 mΩ change
9.3	Temperature cycling	5 cycles (1) -40 °C , 30 min. (2) Room temp. 10-15 min. (3) 105 °C , 30 min. (4) Room temp. 10-15 min.	Appearance: No damage Contact resistance Δ 20 mΩ change

ENGINEERING DEPT.		PRODUCT SPECIFICATION For 2.00 mm (.079") Pin Header of System CH70	SPEC.NO.: SPCH078B
REVISIONS	ECNT120150		PAGE: 3/3

	ITEM	TEST CONDITION	REQUIREMENT
9.4	Salt spray	<p>Temperature: $35 \pm 3^{\circ}\text{C}$ Solution: $5 \pm 1\%$ Spray time: 48 ± 4 hours (Stamping before plated) Spray time: 24 ± 4 hours (Stamping after plated) Mate connectors and expose to the following salt mist conditions. Upon completion of the exposure period, salt deposits shall be removed by a gentle wash or dip in running water and dried naturally, after which the specified measurements shall be performed. The specimens shall be suspended from the top using waxed twine, string or nylon thread. The test only define the plating area, without plating area (as copper cross section) will not be defined. (EIA 364-26B / MIL-STD-202 Method 101)</p>	<p>Appearance: No damage Contact resistance: Less than twice of initial</p>
9.5	Solder ability	<p>DIP Type Lead-Free Process: Soldering time: 3 ± 0.5 second Soldering pot: $240 \pm 5^{\circ}\text{C}$ SMT Type Lead-Free Process: Soldering time: 3 ± 0.5 second Soldering pot: $245 \pm 5^{\circ}\text{C}$</p>	<p>Minimum: 95% of immersed area</p>
9.6	Resistance to soldering heat	<p>Soldering time: 7 ± 3 second Soldering pot: $255 \pm 5^{\circ}\text{C}$</p>	No damage

10. OPERATING TEMPERATURE : -40 to $+105^{\circ}\text{C}$