

<b>ENGINEERING</b>	<b>PRODUCT SPECIFICATION</b>	<b>SPEC.NO.: SPCU028A</b>
<b>DEPT.</b>	<b>HDMI Board Mount Connector (CU11)</b>	<b>PAGE: 1/5</b>

1. SCOPE:

This specification covers performance, tests and quality requirements for the HDMI connector.

2. APPLICABLE STANDARDS:

MIL - STD - 202	Test methods for electrical component parts
MIL - STD - 1344	Test methods for electrical connectors
EIA - RS - 364	Test methods for electrical connectors
J-STD-020	Resistance to soldering Temperature for through hole Mounted Devices
SS-00254	Test methods for electronic components ,LEAD-FREE soldering Part design standards

3. APPLICABLE SERIES NO.: **CU11SAM10E0-R0**

4. SHAPE, CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. ACCOMMODATED P.C.BOARD

6.1 Thickness: 1.6 mm (.063")

6.2 P.C. Board Layout: See attached drawings



REVIEWED : Eisley APPROVED : Eisley VERIFIED : Sandy .




<b>ENGINEERING</b>  <b>DEPT.</b>	<b>PRODUCT SPECIFICATION</b>  <b>HDMI Board Mount Connector (CU11)</b>	<b>SPEC.NO.: SPCU028A</b>
		<b>PAGE: 2/5</b>

**7. ELECTRICAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
7.1	Rated current and voltage		0.5A 40V AC (r.m.s.)
7.2	Contact resistance	Mate connectors Contact: Measure by dry circuit, 20mV max, 10mA. Shell: Measure by open circuit, 5V max, 100mA (EIA-RS-364-23B)	Contact: 30 mΩ Max. (before & after)  Shell: 50 mΩ Max. (before & after)
7.3	Dielectric strength	Mated connectors: Apply 300V AC(r.m.s) for 1 minute between adjacent terminal or ground Unmated connectors: Apply 500V AC(r.m.s) for 1 minute between adjacent terminal or ground (EIA-RS-364-20C)	No Breakdown
7.4	Insulation resistance	Unmated connectors: Apply 500V DC between adjacent terminal or ground Mated connectors: Apply 150V DC between adjacent terminal or ground (EIA-RS-364-21C)	Unmated: 100 MΩ min.  Mated: 10 MΩ min.

**8. MECHANICAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Durability	Measure contact and shell resistance after following. Automatic cycling: Type A:10,000 cycles at 100±50 cycles per hour (EIA-RS-364-09A)	Appearance: No damage  Contact resistance: Contact: 30 mΩ Max. (before & after) Shell: 50 mΩ Max. (before & after)



<b>ENGINEERING</b>  <b>DEPT.</b>	<b>PRODUCT SPECIFICATION</b>	<b>SPEC.NO.: SPCU028A</b>
	<b>HDMI Board Mount Connector (CU11)</b>	<b>PAGE: 3/5</b>

	ITEM	TEST CONDITION	REQUIREMENT
8.2	Insertion / Withdrawal Forces	The force shall be measured with the plug at rate of 25mm/minute. This test shall be made in a direction along the axis of both the socket and the plug. After 4 times, mating force and un-mating force shall be measure. (EIA-RS-364-13A)	Insertion Forces : 4.5 Kgf max. Withdrawal Forces : 1.0 Kgf min.
8.3	Vibration	Amplitude: 1.52mm P-P or 147m/ s <sup>2</sup> (15G) Sweep time: 50-2000-50Hz in 20 minutes. Duration: 12 times in each X、Y、Z axes. (total of 36 times) Electrical load: DC100 mA current shall be flowed during the test. (EIA-RS-364-28)	Appearance: No damage Contact resistance: Contact: 30 mΩ Max. (before & after) Shell: 50 mΩ Max. (before & after) Discontinuity: 1 μsec maximum.

9. ENVIRONMENTAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Solder ability	Soldering time: 5 ± 0.5 second Soldering pot: 245 ± 3°C	Minimum: 95% of immersed area
9.2	Resistance to soldering heat	Soldering time: 10 second. Soldering pot: 250°C Refer Reflow temperature profile(11.1)	Appearance: No evidence of physical damage
9.3	Humidity	The specimens shall be places in a chamber and Subjected to a relative humidity of 90% to 95% and a temperature of 40±2°C for 96 hours then placed in ambient temperature for more than 1 hour. (EIA-RS-364-31A)	Appearance: No damage Contact resistance: Contact: 30 mΩ Max. (before & after) Shell: 50 mΩ Max. (before & after)
9.4	Salt Spray	The specimens shall be subjected to a salt water spray (concentration: 5±1%) at a temperature of 35°C ± 2°C for 24 hours, then placed in ambient temperature for more than 1 hour. (EIA-RS-364-26)	Appearance: No damage Contact resistance: Contact: 30 mΩ Max. (before & after) Shell: 50 mΩ Max. (before & after)

<b>ENGINEERING</b>  <b>DEPT.</b>	<b>PRODUCT SPECIFICATION</b>	<b>SPEC.NO.: SPCU028A</b>
	<b>HDMI Board Mount Connector (CU11)</b>	<b>PAGE: 4/5</b>

	ITEM	TEST CONDITION	REQUIREMENT
9.5	Temperature life (heat)	The specimens shall be subjected to a temperature of 105+ /-2°C for 250 hours, then placed in ambient temperature for more than 3 hours. (MIL-STD-1344A, Method 1005.1)	Appearance: No evidence of physical damage Contact resistance: Contact: 30 mΩ Max. (before & after) Shell: 50 mΩ Max. (before & after)
9.6	Temperature life (cold)	The specimens shall be subjected to a temperature of -25°C for 96 hours, then placed in ambient temperature for more than 3 hours. (MIL-STD-1344A, Method 1005.1)	Appearance: No evidence of physical damage Contact resistance: Contact: 30 mΩ Max. (before & after) Shell: 50 mΩ Max. (before & after)

10. OPERATING TEMPERATURE RANGE: -25°C to +85°C

11. Recommended IR Reflow Temperature Profile:

11.1 Using Lead-Free Solder Paste

